

M-PLANTER



M-160R

"Towards the planting perfection"

Domestic sales:

Antti Meriläinen
+358 400 120 349
antti@m-planter.fi
www.m-planter.fi

Export sales:

Tommi Pyykkönen
+358 40 830 6548
tommi@m-planter.fi
www.m-planter.fi

Post address:

Käenpolku 6
88300 Paltamo
FINLAND

Visiting address:

Konttitie 3
88300 Paltamo
FINLAND

M-Planter M-160R...

- Is a one-headed mounding planter; rips (700-900 mm deep) and plants the seedling, and hydraulically seals the seedling into the soil from two sides.
- Also inserts two granular fertilizers and waters the planted seedling.
- Has enforced body to sustain the stress caused by the ripping.
- Requires an excavator as a base machine. The excavator should be min 16 to 20 ton to ensure efficient ripping ability. The required excavator size depends on the site's soil type and amount of topographic differences (to maintain the balance of the base machine).
- Uses electrically piloted one-way auxiliary hydraulics of the base machine, with 170 bars pressure and 100 l/min flow.

M-160R specs	
Weight	1 150 - 1 500 kg
Width	1 250 mm
Height	1 500 mm
Depth	2 100 mm
Plantingtube \varnothing	60 mm*
Seedling capacity	160 seedlings



* Please note! The seedling reload system can be customized to fit different size seedlings!

M-Planter M-160R standard equipment...

- Adjustable planting depth (120/150 mm) or customized planting depth (200 mm)
- Coupler customized to fit to the client's excavator
- Fertilizer system (for two granular fertilizers)
- Higher seedlingtubes
- Ripper (for 700-900 mm deep ripping)
- Spade/rake (for more efficient harvesting residue sweep ability and additional soil preparation)
- Watering system

M-Planter M-160R optional equipment...

- Cabin camera
- Coupler tilt
- Cultivator discs
- Deep fertilizer system (for third fertilizer to be inserted deep into the soil)
- Herbicide/insecticide/pesticide

